

Ball Knob

with plastic thread

Knob in high-resistance Duroplast allowing for high temperature resistance and durability. Long-lasting and high-tech gloss.


Standard color is black.


T Fastening, plastic thread.

🌡️ Optimum utilisation between -50° to 155° Celsius, Outstanding resistance to chemicals, oil as well as tough climatic conditions.



Ball knob with plastic thread

D	d	B	C	A max.	Reference	 g	Pack
10	M3	9,5	5	5	18.010	2	20 pcs
12	M4	11	6	8	18.011	2	20 pcs
16	M4	15	8	8	18.012	3	20 pcs
16	M5	15	8	10,5	18.013	3	20 pcs
16	M6	15	8	8	863	3	20 pcs
20	M4	18	12	10	2584	5	20 pcs
20	M5	18	12	10	2632	5	20 pcs
20	M6	18	12	12	864	5	20 pcs
20	M8	18	12	12	422	5	20 pcs
25	M5	23,2	15	12	2633	10	20 pcs
25	M6	23,2	15	12	991	10	20 pcs
25	M8	23,2	15	15	993	9	20 pcs
25	M10	23	15	18	18.060	9	20 pcs
32	M6	29	18	13,5	18.015	20	20 pcs
32	M8	29	18	16	18.016	20	20 pcs
32	M10	29	18	21	18.017	18	20 pcs
32	M12	29	18	25	18.061	17	20 pcs
35	M6	32	17	15	1450	27	20 pcs
35	M8	32,8	17	20	1105	27	20 pcs
35	M10	32,8	17	21	1106	26	20 pcs
35	M12	32,8	17	23	1107	25	20 pcs
35	M14	32,8	17	24	1194	25	20 pcs
40	M8	37,3	20	22	926	40	10 pcs
40	M10	37,3	20	23	430	40	10 pcs
40	M12	37,3	20	23	392	39	10 pcs
45	M10	42,6	20	26	1109	52	10 pcs
45	M12	42,6	20	30	1110	51	10 pcs
50	M8	47,5	22	28	1454	70	10 pcs
50	M10	46	27	30	431	69	10 pcs
50	M12	46	27	31	393	68	10 pcs
50	M14	46	27	31	1070	68	10 pcs
60	M16	57	20	30	18.020*	110	10 pcs



Plastic thread version